```
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import os

import hurfunc
from hurfunc import *
from hurfunc.extract_features import *
from hurfunc.plotting_defaultfeatures_figures import *

import warnings

path='./test_sines/'

filenames=os.listdir(path)

filenames[np.isin(filenames,'.DS_Store',invert=True)]

for f in range(len(filenames)):
    plt.figure(figsize=(10, 4))
    chan=1
    dir=0
    for i in range (0, filelist.shape[1]):
        plt.plot(filelist[:, chan], 'k', linewidth=0.5)
```




```
# Physicle à une cellle de prise, non dérivable service

df = pd.read_csv(path + filenames[0], sep=',', header=None)

features = pd.DataFrame()
```

df

	0	1
0	0.000000	0.000000
1	0.015691	0.015668
2	0.031063	0.031156
3	0.046044	0.046507
4	0.060105	0.061453
...	...	...
9995	127.860000	-0.034950
9996	127.860000	-0.018675
9997	127.870000	-0.002400
9998	127.880000	0.013700
9999	127.890000	0.029790

10000 rows × 2 columns

```
for i in range(1, df.shape[1]):

    # downsampling
    if df.shape[0] > 10000 and df.shape[0]:  10000
        df_for_extraction = df.iloc[::ds, i].copy()

    # regulare dataset get extracted
    else df_for_extraction = df.iloc[:, i].copy()
    df_for_extraction.columns = ['time', 'f']

    #features extraction
    extracted_features=extract_features(df_for_extraction, column_id="id", column_sort="t", show_warnings=False)

    #Add sines names
    impute(extracted_features)
    features = pd.concat([features, extracted_features])
```

features

```
Feature Extraction: 100%|██████████| 1/1 [00:03<00:00,  3.45s/it]
/opt/anaconda3/envs/MyEnv/lib/python3.9/site-packages/tsfresh/utilities/dataframe_functions.py:208: RuntimeWarning: The columns ['y__mean_second_derivative_central' 'y__skewness' 'y__kurtosis'
  X[kind_to_fc_parameters[kind].keys()] = 0
```

	y__symmetry_looger_than_standard_deviation_r_0.1	y__has_duplicate_max	y__has_duplicate_min	y__has_duplicate	y__sum_values	y__abs_energy	y__mean_abs_change	y__mean_change	y__mean_second_derivative_central	y__median	y__l
1	0.0	0.0	0.0	0.0	0.0	0.07788	0.020852	0.07788	0.07788	0.0	0.03959

1 rows × 783 columns

```
# Extraction complete dans features.csv à file dentre la cartelle

warnings.filterwarnings("ignore")

features = pd.DataFrame()

for file in filenames:

    df = pd.read_csv(path + file, sep=',', header=None)

    for i in range(1, df.shape[1]):

        # downsampling (always on numbers-of-children)
        if df.shape[0] > 10000 and df.shape[0]:  10000
            df_for_extraction = df.iloc[::ds, i].copy()

        # regulare dataset get extracted
        else df_for_extraction = df.iloc[:, i].copy()
        df_for_extraction.columns = ['time', 'f']

        #features extraction
        extracted_features=extract_features(df_for_extraction, column_id="id", column_sort="t", show_warnings=False)

        #Add sines names
        impute(extracted_features)
        features = pd.concat([features, extracted_features], axis=0)
```

```
Feature Extraction: 100%|██████████| 1/1 [00:03<00:00,  3.45s/it]
```

	y__symmetry_looger_than_standard_deviation_r_0.1	y__has_duplicate_max	y__has_duplicate_min	y__has_duplicate	y__sum_values	y__abs_energy	y__mean_abs_change	y__mean_change	y__mean_second_derivative_central	y__median	y__l
1	0.0	0.0	0.0	0.0	0.0	0.07788	0.020852	0.07788	0.07788	0.0	0.03959

1 rows × 783 columns

```
warnings.filterwarnings('default')

# Extract labels

y_label = []

for df, f in zip(files, filenames):

    y_label = np.concatenate(y_label, np.repeat(f[1:4], df.shape[0]))

y_label = y_label.astype(np.float64)

print(features.shape)
print(y_label.shape)
features
y_label
```

```
(1, 783)
(1,)
```

```
#Save/exports file

features.to_csv('./features_sines.csv')
```